

# SAFETY DATA SHEET

#### 1. Product Identification

**Product name** G2 Glue Hardener, Part B

SDS Number F1110B00

**Product type** Epoxy polymer mixture.

Recommended use of the chemical and

restrictions on use

Directed at, but not limited to, the bonding of similar and dissimilar substrates.

**Restrictions** None known.

Manufacturer/Supplier information

Company nameSYSTEM THREE RESINS, INC.Address3500 W. Valley Hwy, Suite

Suite 105

Auburn, WA 98001-2436

United States

Telephone 1-253-333-8118

Website www.systemthree.com

**Email** support-08@systemthree.com

Emergency Contact CHEMTREC (U.S. and CANADA) 1-800-424-9300 CHEMTREC (Outside the U.S.) 1-703-527-0585

# 2. Hazard(s) Identification

Classification of substance or mixture/Signal Word

DANGER.

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2

Respiratory Sensitization – Category 1 Skin Sensitization – Category 1 Reproductive Toxicity – Category 2

Specific Target Organ Toxicity (Single Exposure) [eyes] – Category 1

Specific Target Organ Toxicity (Single Exposure) [Respiratory tract irritation] -

Category 3

Specific Target Organ Toxicity (Repeated Exposure) [skin, respiratory tract,

kidneys, liver] - Category 1

GHS Label Elements
Hazard Pictograms





Hazard Statements/Classification of substance or mixture

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs: (eyes)

H372 Causes damage to organs through prolonged or repeated exposure:

(skin, respiratory tract, kidneys, liver)

#### **Precautionary statements**

<u>Precautionary Statements</u> P201 Obtain special instructions before use.

**Prevention** P202 Do not handle until all safety precautions have been read and

understood.

P260 Do not breathe vapor.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P271 Use only outdoors or in well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the

workplace.

P280 Wear protective gloves. Wear eye or face protection.

P285 In case of inadequate ventilation wear respiratory protection.

**Response** P314 Get medical attention if you feel unwell.

P308 + P311 If exposed or concerned: Call a POISON CENTER or physician.

**Storage** P405 Store locked up.

**Disposal** P501 Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Hazards not otherwise classified (HNOC)

None Available.

# 3. Composition/Information On Ingredients

Chemical Name	CAS Number	Content (%)
Fatty acids, C18-unsatd., dimers, reaction products	68410-23-1	90 – 100%
with polyethylenepolyamines		
Triethylenetetramine	112-24-3	7 – 10%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

#### 4. First-Aid Measures

**Skin contact** Wash with plenty of soap and water. Remove contaminated clothing and

shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse.

**Eye contact** Flush with water for 15 minutes holding eye lids open. Check for and remove

any contact lenses. Get medical attention. If necessary, call a poison center or

physician.

**Ingestion** Wash out mouth with water. Remove dentures if any. Remove victim to fresh

air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person in conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention

immediately. Maintain an open airway. Loosen tight clothing such as collar,

tie, belt, or waistband.

**Inhalation** Remove victim to fresh air and provide oxygen if breathing is difficult. Give

artificial respiration if not breathing. Get medical attention.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** In case of inhalation of decomposition products in a fire, symptoms may be

delayed. The exposed person may need to be kept under medical surveillance

for 48 hours.

**Specific treatments** Treat symptoms as they appear.

## 5. Fire-Fighting Measures

**Suitable extinguishing media** Foam, carbon dioxide, dry chemical, water fog.

**Unsuitable extinguishing media** None known.

**Specific hazards arising from the chemical** In a fire or if heated, a pressure increase will occur and the container may

burst.

Hazardous decomposition products
Special protective actions for fire-fighters

Carbon oxides, nitrogen oxides.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk

or without suitable training.

Special protective equipment for fire-

fighters

**Further information** 

Full fire suit and self-contained breathing apparatus.

None known.

#### 6. Accidental Release Measures

**Personal precautions**Wear proper personal protective equipment (PPE). Avoid direct contact with

material. Proper PPE includes: disposable gloves, eye protection and skin

protection.

**Emergency procedures** If material is spilled, avoid contact with material. Persons not wearing

appropriate protective equipment should leave the area of the spill until

cleanup is complete.

Methods and materials for

containment/cleanup

Stop spill at source, dike area to prevent spreading, pump liquid to salvage tank or drum. Remaining liquid may be taken up on clay, diatomaceous earth,

sawdust or other absorbent, and shoveled into disposal container.

**Environmental precautions** Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform relevant authorities if the product has

caused environmental pollution (sewers, waterways, soil or air).

## 7. Handling and Storage

Precautions for safe handling Always wear protective, disposable gloves when handling epoxy products to

prevent exposure. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is

inadequate.

Precautions/Recommendations for

safe/proper storage

Store epoxy products in temperature stable environment, out of the reach of pets or children. Securely fasten container lids and tops, and prevent products

from sitting and below freezing temperatures.

## 8. Exposure Controls/Personal Protection

Occupational Exposure Limits

Triethylenetetramine
AIHA WEEL (1999-01-01)
Time Weighted Average (TWA) 1 ppm
NIOSH REL (2005-09-30)

**Appropriate engineering controls** If user operations generate dust, fumes, gas, vapor or mist, use process

enclosures, local ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory

limits.

**Environmental exposure controls**Use appropriate containment to avoid environmental contamination. Do not

allow spill to enter sewers or waterways.

Individual protection measures/Personal

protective equipment

**Eye/face protection** Splash proof goggles or safety glasses with side shields are recommended.

Always wear eye protection when sanding cured epoxy to avoid dust in eyes.

**Hand protection** Always wear impervious gloves, neoprene, vinyl or rubber. **Skin protection** Wear clean, body-covering clothing to avoid skin contact.

**Respiratory protection**Use a NIOSH-approved respiratory device when sanding cured epoxy to

prevent dust in lungs.

Special instructions for protection and

hygiene

Wear gloves at all times when handling product, avoid direct contact with skin. When finished using product, dispose of gloves properly and wash hands

with warm, soapy water.

## 9. Physical and Chemical Properties

Chemical family Polyamide curing agent

Appearance Viscous liquid

Physical State Epoxy polymer mixture

Form Liquid

Color Reddish-brown
Odor Characteristic

 Density
 970 kg/m3 (8.09 lb/gal)

 Viscosity
 13,000 CPS @ 25°C (77°F)

pH N/A

Melting point/freezing pointData not availableInitial boiling point and boiling rangeData not available

Flash point Open cup: >110°C (230°F), ASTM D 4206

Evaporation rate Data not available
Flammability (solid, gas) Data not available

Upper/lower flammability limit (by volume)

Upper flammability limit (by volume) N/A

Lower flammability limit (by volume) N/A

Material VOC None

Vapor density 1 [Air=1]

Relative density Not determined

Solubility in water Slightly

Partition coefficient: n-octanol/waterData not availableAuto-ignition temperatureData not availableDecomposition temperatureData not available

## 10. Stability and Reactivity

**Reactivity** Stable under normal conditions.

Chemical Stability Stable

**Possibility of hazardous reactions** Hazardous polymerization will not occur.

Conditions to avoid Avoid exposure – obtain special instructions before use. Avoid all possible

sources of ignition (spark or flame).

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition products**Under normal conditions or storage and use, hazardous decomposition

products should not be produced.

Other hazards Heating this substance above 300°F in the presence of air may cause slow

oxidative decomposition; above 500°F polymerization may occur. Some combinations of resins and curing agents can produce exothermic reactions which in large masses can cause runaway polymerization and charring of the reactants. Fumes and vapors from the thermal and chemical decompositions

vary widely in composition and toxicity.

# 11. Toxicological Information

#### **Acute Health Hazard (components)**

No comprehensive data (ingestion, inhalation, dermal) on mixture (product).

Component	Result	Species	Dose	Exposure
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	LD50 Oral	Rat	>5,000 mg/kg	-
Triethylenetetramine	LD50 Oral	Rat	2,500 mg/kg	-

#### Irritation/Corrosion (components)

No information on product itself.

Component	Result	Species	Score	Exposure
Triethylenetetramine	Eyes – Moderate irritant	Rabbit		24 hrs
	Skin – Severe irritant	Rabbit		24 hrs
	Eyes – Severe irritant	Rabbit		

SensitizationNo information on product itself.MutagenicityNo information on product itself.CarcinogenicityNo information on product itself.Reproductive ToxicityNo information on product itself.

Teratogenicity No information on product itself.

# Specific target organ toxicity (single exposure)

No information on product itself.

Component	Category	Route of exposure	Target organs
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	Category 3		Respiratory tract irritation
Triethylenetetramine	Category 1		Eyes

Specific target organ toxicity (repeated

No information on product itself.

exposure)

Component	Category	Route of exposure	Target organs
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	Category 2		Skin
Triethylenetetramine	Category 1 Category 2		Respiratory tract Skin
			Liver Kidneys

Aspiration hazard No information on product itself.

Potential acute health effects

**Eye Contact** Causes serious eye irritation.

**Inhalation** May cause respiratory irritation. May cause allergy or asthma symptoms or

breathing difficulties if inhaled. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

**Skin Contact** Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical

and toxicological characteristics

**Eye Contact** Adverse symptoms may include the following:

Pain Watering Redness

**Inhalation** Adverse symptoms may include the following:

Respiratory tract irritation

Coughing

Wheezing and breathing difficulties

Asthma

Reduced fetal weight Increase in fetal deaths Skeletal malformations

**Skin Contact** Adverse symptoms may include the following:

Irritation Redness

Reduced fetal weight Increase in fetal deaths Skeletal malformations

**Ingestion** Adverse symptoms may include the following:

Reduced fetal weight Increase in fetal deaths Skeletal malformations

### <u>Delayed and immediate effects and also</u> <u>chronic effects from short and long term</u> <u>exposure</u>

#### Potential chronic health effects

**General** Causes damage to organs through prolonged or repeated exposure: Once

sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

**Carcinogenicity** No known significant effects or critical hazards.

**Mutagenicity** No known significant effects or critical hazards.

**Teratogenicity** Suspected of damaging the unborn child.

**Developmental effects** No known significant effects or critical hazards.

**Fertility effects** Suspected of damaging fertility.

**Numerical measures of toxicity** 

Acute toxicity estimates (ATEmix) Not available.

Route	ATE value
Oral	N/A
Dermal	N/A
Inhalation (vapors)	N/A

## 12. Ecological Information

#### **Ecotoxicity**

Component	Result	Species	Exposure
Triethylenetetramine	Acute LC50 – 33,900 μg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 – 3,700 μg/l Fresh water	Aquatic plants – Green algae	96 h

<u>Persistence and degradability</u> No information on product itself.

<u>Bioaccumulative Potential</u> No information on product itself.

Component	LogPow	BCF	Potential
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines		492.00	Low
Triethylenetetramine	-1.661.4	-	low

#### **Mobility in Soil**

**Soil/water partition coefficient (KOC)**No information on product itself.

Other adverse effects No known significant effects or critical hazards.

# 13. Disposal Considerations

Waste from residues/ unused products

The generation of waste should be avoided or minimized wherever possible. Product should not be allowed to enter drains, water courses or the soil; dispose of this material and its containers in a safe way. Contact supplier if guidance is required.

and local requirements.

## 14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

#### **International Transport Regulations**

Regulatory information	UN/NA number	Proper Shipping Name	Classes/*PG	Additional Information
DOT		Not regulated		
TDG		Not regulated		
IMO/IMDG		Not regulated		
IATA (Cargo)		Not regulated		

\*PG: Packing group

Special precautions for user: Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to

do in the event of an accident or spillage.

## 15. Regulatory Information

#### **UNITED STATES**

U.S. Federal Regulations United States – TSCA 12(b) – Chemical export notification: None Required.

United States – TSCA 5(a)2 – Final significant new use rules: Not Listed.
United States – TSCA 5(a)2 – Proposed significant new use rules: Not Listed.

**United States – TSCA 5(e) – Substance consent order:** Not listed.

California Prop. 65 None required.

**EPA SARA 302 Extremely Hazardous** None required.

Substances

EPA SARA 302/304/311/312 Hazardous None required.
Chemicals

United States inventory (TSCA 8b) All components are listed or exempted.

**CANADA** 

WHMIS (Canada) Class D-2B: Material causing other toxic effects (Toxic).

Canadian NPRINone required.CEPA Toxic substancesNone required.

INTERNATIONAL REGULATIONS

International Lists Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted.

Korea inventory: All components are listed or exempted.

Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

New Zealand inventory (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

Taiwan inventory (CSNN): All components are listed or exempted.

# 16. Other Information, Including Date of Preparation or Last Revision

#### **HMIS Rating**



**Date of Preparation** December 21, 2016

**Date of Last Revision** 

Revision # 1.0

More Information 1-253-333-8118

**Prepared by**N. Kim, System Three Resins Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.